

CVS/Caremark

Implementation Guide

810 – Distribution Center Invoice

Version X12-4010

Table of Contents

810	Invoice	4
ISA	Interchange Control Header	5
GS	Functional Group Header	7
ST	Transaction Set Header	9
BIG	Beginning Segment for Invoice	10
REF	Reference Identification	11
N1	Loop Name	12
N1	Name	13
ITD	Terms of Sale/Deferred Terms of Sale	14
DTM	Date/Time Reference	15
FOB	F.O.B. Related Instructions	17
IT1	Loop Baseline Item Data (Invoice)	17
IT1	Baseline Item Data (Invoice)	18
PID	Loop Product/Item Description	23
PID	Product/Item Description	27
PO4	Item Physical Details	22
TDS	Total Monetary Value Summary	23
SAC	Loop Service, Promotion, Allowance, or Charge Information	24
SAC	Service, Promotion, Allowance, or Charge Information	25
ISS	Loop Invoice Shipment Summary	27
ISS	Invoice Shipment Summary	28
CTT	Transaction Totals	29
SE	Transaction Set Trailer	30
GE	Functional Group Trailer	31
IEA	Interchange Control Trailer	32

EDI provides an efficient means for our trading partner to submit invoices for payment. Receipt of the invoices, as well as an indication of any EDI-related processing problems that occur, will be conveyed back to the vendor via Functional Acknowledgments (997). The 'FAs' will be automatically sent back for each inbound document.

Once received and processed through the EDI systems, the invoices are transferred to the Accounts Payable processes. If any errors occur within the Accounts Payable systems, an Application Advice (824) will be sent to the vendor and the invoice will not be paid. The error(s) will then have to be rectified, and the corrected invoice(s) retransmitted to CVS. ONLY the corrected invoices should be retransmitted.

IT IS MANDATORY TO TRADE THE APPLICATION ADVICE (824) WHEN CONDUCTING ELECTRONIC INVOICING.

AP Invoice Matching System Criteria...

The Accounts Payable department utilizes a matching system that performs a detailed, systemic comparative match by line item between a supplier's EDI invoice and the internal CVS PO and receipt. The program compares, for each item, units received against units billed, and unit price on the PO compared to unit price on the invoice. In order to accomplish this detailed match, CVS re-computes the extended cost for each line item as follows:

Units Calculation:

(Cases, dozens, each) * Pack Quantity = Number of Pieces Shipped

Cost Calculation:

EDI Invoice Cost / Pack Quantity = Piece Cost

Extended Cost Calculation:

Number of Pieces Shipped * Piece Cost = Extended Cost

Obviously, matching discrepancies arise when the above calculations do not match the invoiced amount per line item. Discrepancies such as these will result in payment shortages due to invalid data on the EDI invoice. The invalid invoice information, primarily centered around case pack errors, can cause significant delays in a supplier receiving proper payment. In addition, additional workloads at CVS and in your company's credit department are created. It is in both of our companies' interest to get the EDI invoice information correct.

This affects not all of our suppliers, however, we ask each of our suppliers to review their EDI invoice data elements and ensure the invoiced amount per line item on an EDI invoice is supported by the above calculations. If not, we ask that you make the appropriate correction(s) immediately. Failure to do so will result in payment discrepancies. If there are any questions regarding the correction of EDI invoices, please contact the EDI Department by email at EDIAPMailbox@cvs.com.

Note that it is MANDATORY to trade the Application Advice (824) when conducting electronic invoicing.

810

Invoice

Functional Group=IN

Purpose: This Draft Standard for Trial Use contains the format and establishes the data contents of the Invoice Transaction Set (810) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide for customary and established business and industry practice relative to the billing for goods and services provided.

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	ISA	Interchange Control Header	M	1			Must use
	GS	Functional Group Header	M	1			Must use

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	ST	Transaction Set Header	M	1			Must use
020	BIG	Beginning Segment for Invoice	M	1			Must use
050	REF	Reference Identification	O	12			Must use
LOOP ID - N1					200		
070	N1	Name	O	1			Must use
130	ITD	Terms of Sale/Deferred Terms of Sale	O	>1			Must use
140	DTM	Date/Time Reference	O	10			Must use

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOP ID - IT1					200000		
010	IT1	Baseline Item Data (Invoice)	O	1			Must use
100	PO4	Item Physical Details	O	1			Must use

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	TDS	Total Monetary Value Summary	M	1			Must use
LOOP ID - ISS					>1		
060	ISS	Invoice Shipment Summary	O	1			Must use
070	CTT	Transaction Totals	O	1		N3/070	Must use
080	SE	Transaction Set Trailer	M	1			Must use

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	GE	Functional Group Trailer	M	1			Must use
	IEA	Interchange Control Trailer	M	1			Must use

Notes:

3/070 Number of line items (CTT01) is the accumulation of the number of IT1 segments. If used, hash total (CTT02) is the sum of the value of quantities invoiced (IT102) for each IT1 segment.

ISA Interchange Control Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 16

User Option (Usage): Must use

Purpose: To start and identify an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA01	I01	Authorization Information Qualifier	M	ID	2/2	Must use

Description: Code to identify the type of information in the Authorization Information

CodeList Summary (Total Codes: 7, Included: 1)

<u>Code</u>	<u>Name</u>
00	No Authorization Information Present (No Meaningful Information in I02)

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA02	I02	Authorization Information	M	AN	10/10	Must use

Description: Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)

ISA03	I03	Security Information Qualifier	M	ID	2/2	Must use
-------	-----	--------------------------------	---	----	-----	----------

Description: Code to identify the type of information in the Security Information

CodeList Summary (Total Codes: 2, Included: 1)

<u>Code</u>	<u>Name</u>
00	No Security Information Present (No Meaningful Information in I04)

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA04	I04	Security Information	M	AN	10/10	Must use

Description: This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)

ISA05	I05	Interchange ID Qualifier	M	ID	2/2	Must use
-------	-----	--------------------------	---	----	-----	----------

Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified

CodeList Summary (Total Codes: 38, Included: 1)

<u>Code</u>	<u>Name</u>
01	Duns (Dun & Bradstreet)

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA06	I06	Interchange Sender ID	M	AN	15/15	Must use

Description: Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element

ISA07	I05	Interchange ID Qualifier	M	ID	2/2	Must use
-------	-----	--------------------------	---	----	-----	----------

Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified

CodeList Summary (Total Codes: 38, Included: 1)

<u>Code</u>	<u>Name</u>
ZZ	Mutually Defined

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
------------	-----------	---------------------	------------	-------------	----------------	--------------

ISA08	I07	Interchange Receiver ID	M	AN	15/15	Must use
		Description: Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID, thus other parties sending to them will use this as a receiving ID to route data to them				
ISA09	I08	Interchange Date	M	DT	6/6	Must use
		Description: Date of the interchange				
ISA10	I09	Interchange Time	M	TM	4/4	Must use
		Description: Time of the interchange				
ISA11	I10	Interchange Control Standards Identifier	M	ID	1/1	Must use
		Description: Code to identify the agency responsible for the control standard used by the message that is enclosed by the interchange header and trailer All valid standard codes are used. (Total Codes: 1)				
ISA12	I11	Interchange Control Version Number	M	ID	5/5	Must use
		Description: Code specifying the version number of the interchange control segments				
		CodeList Summary (Total Codes: 14, Included: 1)				
		<u>Code</u>		<u>Name</u>		
		0401		Draft Standards for Trial Use Approved for Publication by ASC X12 Procedures Review Board through October 1997		
<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA13	I12	Interchange Control Number	M	N0	9/9	Must use
		Description: A control number assigned by the interchange sender				
ISA14	I13	Acknowledgment Requested	M	ID	1/1	Must use
		Description: Code sent by the sender to request an interchange acknowledgment (TA1)				
		CodeList Summary (Total Codes: 2, Included: 1)				
		<u>Code</u>		<u>Name</u>		
		0		No Acknowledgment Requested		
<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA15	I14	Usage Indicator	M	ID	1/1	Must use
		Description: Code to indicate whether data enclosed by this interchange envelope is test, production or information				
		CodeList Summary (Total Codes: 3, Included: 1)				
		<u>Code</u>		<u>Name</u>		
		P		Production Data		
<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA16	I15	Component Element Separator	M		1/1	Must use
		Description: Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator				

GS**Functional Group Header**

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 8

User Option (Usage): Must use**Purpose:** To indicate the beginning of a functional group and to provide control information**Element Summary:**

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS01	479	Functional Identifier Code	M	ID	2/2	Must use

Description: Code identifying a group of application related transaction sets**CodeList Summary** (Total Codes: 240, Included: 1)

<u>Code</u>	<u>Name</u>
IN	Invoice Information (810,819)

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS02	142	Application Sender's Code	M	AN	2/15	Must use

Description: Code identifying party sending transmission; codes agreed to by trading partners

GS03	124	Application Receiver's Code	M	AN	2/15	Must use
------	-----	------------------------------------	---	----	------	----------

Description: Code identifying party receiving transmission; codes agreed to by trading partners

GS04	373	Date	M	DT	8/8	Must use
------	-----	-------------	---	----	-----	----------

Description: Date expressed as CCYYMMDD

GS05	337	Time	M	TM	4/8	Must use
------	-----	-------------	---	----	-----	----------

Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)

GS06	28	Group Control Number	M	N0	1/9	Must use
------	----	-----------------------------	---	----	-----	----------

Description: Assigned number originated and maintained by the sender

GS07	455	Responsible Agency Code	M	ID	1/2	Must use
------	-----	--------------------------------	---	----	-----	----------

Description: Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480**CodeList Summary** (Total Codes: 2, Included: 1)

<u>Code</u>	<u>Name</u>
X	Accredited Standards Committee X12

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS08	480	Version / Release / Industry Identifier Code	M	AN	1/12	Must use

Description: Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed**CodeList Summary** (Total Codes: 39, Included: 1)

<u>Code</u>	<u>Name</u>
004010	Draft Standards Approved for Publication by ASC X12 Procedures Review Board through October 1997

Semantics:

1. GS04 is the group date.
2. GS05 is the group time.

3. The data interchange control number GS06 in this header must be identical to the same data element in the associated functional group trailer, GE02.

Comments:

1. A functional group of related transaction sets, within the scope of X12 standards, consists of a collection of similar transaction sets enclosed by a functional group header and a functional group trailer.

ST Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use

Description: Code uniquely identifying a Transaction Set

CodeList Summary (Total Codes: 298, Included: 1)

<u>Code</u>	<u>Name</u>
810	Invoice

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST02	329	Transaction Set Control Number	M	AN	4/9	Must use

Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set

Semantics:

- The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

BIG Beginning Segment for Invoice

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 4

User Option (Usage): Must use

Purpose: To indicate the beginning of an invoice transaction set and transmit identifying numbers and dates

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BIG01	373	Date	M	DT	8/8	Must use
		Description: Date expressed as CCYYMMDD				
BIG02	76	Invoice Number	M	AN	1/22	Must use
		Description: Identifying number assigned by issuer Vendor's Invoice Number				
BIG03	373	Date	O	DT	8/8	Must use
		Description: Date expressed as CCYYMMDD				
BIG04	324	Purchase Order Number	O	AN	1/22	Must use
		Description: Identifying number for Purchase Order assigned by the orderer/purchaser CVS P.O. # being Invoiced				
BIG07	640	Transaction Type Code	O	ID	2/2	Must use
		Description: Code specifying the type of Transaction For Credits: 'CR' or 'CN' acceptable				

Semantics:

1. BIG01 is the invoice issue date.
2. BIG03 is the date assigned by the purchaser to purchase order.
3. BIG10 indicates the consolidated invoice number. When BIG07 contains code CI, BIG10 is not used.

Comments:

1. BIG07 is used only to further define the type of invoice when needed.

REF Reference Identification

Pos: 050	Max: 12
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Must use
Purpose: To specify identifying information

IT IS MANDATORY TO SEND REF SEGMENT INCLUDING REF02 FOR 810 – INVOICE.

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

CodeList Summary (Total Codes: 1503, Included: 1)

<u>Code</u>	<u>Name</u>
VR	Vendor ID Number

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF02	127	Reference Identification	X	AN	1/30	Must use

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier
 CVS Vendor Number

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

Loop Name

Pos: 070	Repeat: 200
	Optional
Loop: N1	Elements: N/A

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
070	N1	Name	O	1		Must use

N1	Name	Pos: 070	Max: 1
		Heading - Optional	
		Loop: N1	Elements: 3

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use

Description: Code identifying an organizational entity, a physical location, property or an individual

CodeList Summary (Total Codes: 1312, Included: 1)

<u>Code</u>	<u>Name</u>
ST	Ship To
RE	Party to receive commercial invoice remittance

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N103	66	Identification Code Qualifier	X	ID	1/2	Must use

Description: Code designating the system/method of code structure used for Identification Code (67)

CodeList Summary (Total Codes: 215, Included: 1)

<u>Code</u>	<u>Name</u>
54	Warehouse (Use if Front Store OTC Items)
11	Use if Pharmacy (DEA Number)

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N104	67	Identification Code	X	AN	2/80	Must use

Description: Code identifying a party or other code

If N103 = '54' - 4 Character Warehouse Code (See Distribution Center ID Table for Ship-to-location)

If N103 = '11' - (See DEA Codes Table for Ship-to-location)

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

ITD Terms of Sale/Deferred Terms of Sale

Pos: 130	Max: >1
Heading - Optional	
Loop: N/A	Elements: 6

User Option (Usage): Must use

Purpose: To specify terms of sale

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ITD01	336	Terms Type Code	O	ID	2/2	Must use

Description: Code identifying type of payment terms

CodeList Summary (Total Codes: 65, Included: 1)

<u>Code</u>	<u>Name</u>
01	Basic
02	End of Month (EOM)
04	Deferred or Installment
07	Extended

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ITD02	333	Terms Basis Date Code	O	ID	1/2	Must use

Description: Code identifying the beginning of the terms period

CodeList Summary (Total Codes: 17, Included: 1)

<u>Code</u>	<u>Name</u>
15	Receipt of Goods
4	Specified Date

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ITD03	338	Terms Discount Percent	O	R	1/6	Used

Description: Terms discount percentage, expressed as a percent, available to the purchaser if an invoice is paid on or before the Terms Discount Due Date

ITD05	351	Terms Discount Days Due	X	N0	1/3	Used
-------	-----	-------------------------	---	----	-----	------

Description: Number of days in the terms discount period by which payment is due if terms discount is earned

ITD07	386	Terms Net Days	O	N0	1/3	Used
-------	-----	----------------	---	----	-----	------

Description: Number of days until total invoice amount is due (discount not applicable)

ITD10	389	Deferred Amount Due	X	N2	1/10	Used
-------	-----	---------------------	---	----	------	------

Description: Deferred amount due for payment

Syntax Rules:

- 1.L03040513 - If ITD03 is present, then at least one of ITD04, ITD05 or ITD13 is required.
- 2.L08040513 - If ITD08 is present, then at least one of ITD04, ITD05 or ITD13 is required.
- 3.L091011 - If ITD09 is present, then at least one of ITD10 or ITD11 is required.

Semantics:

1. ITD15 is the percentage applied to a base amount used to determine a late payment charge.

Comments:

1. If the code in ITD01 is "04", then ITD07 or ITD09 is required and either ITD10 or ITD11 is required; if the code in ITD01 is "05", then ITD06 or ITD07 is required.

DTM Date/Time Reference

Pos: 140	Max: 10
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Must use
Purpose: To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use

Description: Code specifying type of date or time, or both date and time

CodeList Summary (Total Codes: 1112, Included: 1)

<u>Code</u>	<u>Name</u>
011	Shipped

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM02	373	Date	X	DT	8/8	Must use

Description: Date expressed as CCYYMMDD

Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.
3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

FOB F.O.B. Related Instructions

Pos: 150	Max: 1
Heading - Optional	
Loop: N/A	Elements: 3

User Option (Usage): Must use

Purpose: To specify transportation instructions relating to shipment

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
FOB01	146	Shipment Method of Payment	M	ID	2/2	Must use

Description: Code identifying payment terms for transportation charges

CodeList Summary (Total Codes: 28, Included: 1)

<u>Code</u>	<u>Name</u>
BP	Paid by Buyer
CC	Collect
FO	FOB Port of Call
BP	Backhaul
PC	Prepaid but Charged to Customer
PP	Prepaid (by Seller)
TP	Third Party Pay

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
FOB02	309	Location Qualifier	X	ID	1/2	Must use

Description: Code identifying type of location

CodeList Summary (Total Codes: 172, Included: 1)

<u>Code</u>	<u>Name</u>
OR	Origin (Shipping Point)

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
FOB03	352	Description	O	AN	1/80	Must use

Description: A free-form description to clarify the related data elements and their content

Syntax Rules:

1. C0302 - If FOB03 is present, then FOB02 is required.
2. C0405 - If FOB04 is present, then FOB05 is required.
3. C0706 - If FOB07 is present, then FOB06 is required.
4. C0809 - If FOB08 is present, then FOB09 is required.

Semantics:

1. FOB01 indicates which party will pay the carrier.
2. FOB02 is the code specifying transportation responsibility location.
3. FOB06 is the code specifying the title passage location.
4. FOB08 is the code specifying the point at which the risk of loss transfers. This may be different than the location specified in FOB02/FOB03 and FOB06/FOB07.

Loop Baseline Item Data (Invoice)

Pos: 010	Repeat: 200000
	Optional
Loop: IT1	Elements: N/A

User Option (Usage): Must use

Purpose: To specify the basic and most frequently used line item data for the invoice and related transactions

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	IT1	Baseline Item Data (Invoice)	O	1		Must use
100	PO4	Item Physical Details	O	1		Must use

IT1 Baseline Item Data (Invoice)

Pos: 010	Max: 1
Detail - Optional	
Loop: IT1	Elements: 8

User Option (Usage): Must use

Purpose: To specify the basic and most frequently used line item data for the invoice and related transactions

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IT102	358	Quantity Invoiced	X	R	1/10	Must use

Description: Number of units invoiced (supplier units)

IT103	355	Unit or Basis for Measurement Code	X	ID	2/2	Must use
-------	-----	------------------------------------	---	----	-----	----------

Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken

CodeList Summary (Total Codes: 794, Included: 1)

<u>Code</u>	<u>Name</u>
CA	Case
PC	Piece
EA	Each
DZ	Dozen

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IT104	212	Unit Price	X	R	1/17	Must use

Description: Price per unit of product, service, commodity, etc.

IT105	639	Basis of Unit Price Code	O	ID	2/2	Must use
-------	-----	--------------------------	---	----	-----	----------

Description: Code identifying the type of unit price for an item

CodeList Summary (Total Codes: 91, Included: 1)

<u>Code</u>	<u>Name</u>
CP	Current Price (Subject to Change)
DS	Discount
PR	Promotion

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IT106	235	Product/Service ID Qualifier	X	ID	2/2	Must use

Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)

CodeList Summary (Total Codes: 477, Included: 1)

<u>Code</u>	<u>Name</u>
UI	U.P.C. Consumer Package Code (1-5-5)
ND	If RX – ND (NDC)
UD	U.P.C/EAN Consumer Package Code (2-5-5)

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IT107	234	Product/Service ID	X	AN	1/48	Must use

Description: Identifying number for a product or service

Item UPC Number or EAN

If RX – NDC Code

If no UPC is available, will be Purchaser’s Item Number (6 characters)

IT108	235	Product/Service ID Qualifier	X	ID	2/2	Must use
-------	-----	------------------------------	---	----	-----	----------

Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)

CodeList Summary (Total Codes: 477, Included: 1)

<u>Code</u>	<u>Name</u>
UA	U.P.C./EAN Case Code (2-5-5) (Optional)

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IT109	234	Product/Service ID	X	AN	1/48	Must use

Description: Identifying number for a product or service
Case UPC Code (Optional)

IT110	235	Product/Service ID Qualifier	X	ID	2/2	Must use
-------	-----	------------------------------	---	----	-----	----------

Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)

CodeList Summary (Total Codes: 477, Included: 1)

<u>Code</u>	<u>Name</u>
PI	Purchaser's Item Code (Required)

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IT111	234	Product/Service ID	X	AN	1/48	Must use

Description: Identifying number for a product or service
CVS Item Number (Required)

Syntax Rules:

1. P020304 - If either IT102, IT103 or IT104 are present, then the others are required.
2. P0607 - If either IT106 or IT107 is present, then the other is required.
3. P0809 - If either IT108 or IT109 is present, then the other is required.
4. P1011 - If either IT110 or IT111 is present, then the other is required.
5. P1213 - If either IT112 or IT113 is present, then the other is required.
6. P1415 - If either IT114 or IT115 is present, then the other is required.
7. P1617 - If either IT116 or IT117 is present, then the other is required.
8. P1819 - If either IT118 or IT119 is present, then the other is required.
9. P2021 - If either IT120 or IT121 is present, then the other is required.
10. P2223 - If either IT122 or IT123 is present, then the other is required.
11. P2425 - If either IT124 or IT125 is present, then the other is required.

Semantics:

1. IT101 is the purchase order line item identification.

Comments:

1. Element 235/234 combinations should be interpreted to include products and/or services. See the Data Dictionary for a complete list of IDs.
2. IT106 through IT125 provide for ten different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

Loop Product/Item Description

Pos: 060	Repeat: 1000
	Optional
Loop: PID	Elements: N/A

User Option (Usage): Must use

Purpose: To describe a product or process in coded or free-form format

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
060	PID	Product/Item Description	O	1		Must use

PID	Product/Item Description	Pos: 060	Max: 1
		Detail - Optional	
		Loop: PID	Elements: 2

PO4 Segment must be sent only if IT103 (Unit of Measure) = ‘CA’ or ‘DZ’.
Please, don’t send it when IT103 = ‘PC’ or ‘EA’. If sent case pack value must be 1.

User Option (Usage): Must use
Purpose: To describe a product or process in coded or free-form format

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PID01	349	Item Description Type	M	ID	1/1	Must use

Description: Code indicating the format of a description

CodeList Summary (Total Codes: 3, Included: 1)

<u>Code</u>	<u>Name</u>
F	Free-form

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PID05	352	Description	X	AN	1/80	Must use

Description: A free-form description to clarify the related data elements and their content
 Item Description

Syntax Rules:

1. C0403 - If PID04 is present, then PID03 is required.
2. R0405 - At least one of PID04 or PID05 is required.
3. C0703 - If PID07 is present, then PID03 is required.
4. C0804 - If PID08 is present, then PID04 is required.
5. C0905 - If PID09 is present, then PID05 is required.

Semantics:

1. Use PID03 to indicate the organization that publishes the code list being referred to.
2. PID04 should be used for industry-specific product description codes.
3. PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
4. PID09 is used to identify the language being used in PID05.

Comments:

1. If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
2. Use PID06 when necessary to refer to the product surface or layer being described in the segment.
3. PID07 specifies the individual code list of the agency specified in PID03.

PO4 Item Physical Details

Pos: 100	Max: 1
Detail - Optional	
Loop: IT1	Elements: 1

User Option (Usage): Must use

Purpose: To specify the physical qualities, packaging, weights, and dimensions relating to the item

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PO401	356	Pack	O	NO	1/6	Must use

Description: The number of inner containers, or number of eaches if there are no inner containers, per outer container

CVS ordered Case Pack (Number of selling Units per Case)

Syntax Rules:

1. P0203 - If either PO402 or PO403 is present, then the other is required.
2. C0506 - If PO405 is present, then PO406 is required.
3. P0607 - If either PO406 or PO407 is present, then the other is required.
4. P0809 - If either PO408 or PO409 is present, then the other is required.
5. C1013 - If PO410 is present, then PO413 is required.
6. C1113 - If PO411 is present, then PO413 is required.
7. C1213 - If PO412 is present, then PO413 is required.
8. L13101112 - If PO413 is present, then at least one of PO410, PO411 or PO412 is required.
9. C1716 - If PO417 is present, then PO416 is required.
10. C1804 - If PO418 is present, then PO404 is required.

Semantics:

1. PO415 is used to indicate the relative layer of this package or range of packages within the layers of packaging. Relative Position 1 (value R1) is the innermost package.
2. PO416 is the package identifier or the beginning package identifier in a range of identifiers.
3. PO417 is the ending package identifier in a range of identifiers.
4. PO418 is the number of packages in this layer.

Comments:

1. PO403 - The "Unit or Basis for Measure Code" in this segment position is for purposes of defining the pack (PO401) /size (PO402) measure which indicates the quantity in the inner pack unit. For example: If the carton contains 24 12-Ounce packages, it would be described as follows: Data element 356 = "24"; Data element 357 = "12"; Data element 355 = "OZ".
2. PO413 defines the unit of measure for PO410, PO411, and PO412.

TDS Total Monetary Value Summary

Pos: 010	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To specify the total invoice discounts and amounts

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TDS01	610	Amount Description: Monetary amount Total Invoice. The amount of invoice (including charges, less allowances) before terms discount, if applicable.	M	N2	1/15	Must use
TDS02	610	Amount Description: Monetary amount Invoice Amount subject to discount. The amount upon which the terms discount amount is calculated.	O	N2	1/15	Must use
TDS03	610	Amount Description: Monetary amount The amount of invoice due if paid by terms discount due date (total invoice amount less cash discount).	O	N2	1/15	Must use
TDS04	610	Amount Description: Monetary amount The total amount of terms discount.	O	N2	1/15	Must use

Semantics:

1. TDS01 is the total amount of invoice (including charges, less allowances) before terms discount (if discount is applicable).
2. TDS02 indicates the amount upon which the terms discount amount is calculated.
3. TDS03 is the amount of invoice due if paid by terms discount due date (total invoice or installment amount less cash discount).
4. TDS04 indicates the total amount of terms discount.

Comments:

1. TDS02 is required if the dollar value subject to discount is not equal to the dollar value of TDS01.

Loop Service, Promotion, Allowance, or Charge Information

Pos: 040	Repeat: 25
Optional	
Loop: SAC	Elements: N/A

User Option (Usage): Must use

Purpose: To request or identify a service, promotion, allowance, or charge; to specify the amount or percentage for the service, promotion, allowance, or charge

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
040	SAC	Service, Promotion, Allowance, or Charge Information	O	1		Must use

SAC Service, Promotion, Allowance, or Charge Information

Pos: 040	Max: 1
Summary - Optional	
Loop: SAC	Elements: 5

If SAC Segment is sent as Header on 850 – Purchase Order, it needs to be sent as Summary on 810 – DC Invoice.

User Option (Usage): Must use

Purpose: To request or identify a service, promotion, allowance, or charge; to specify the amount or percentage for the service, promotion, allowance, or charge

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SAC01	248	Allowance or Charge Indicator	M	ID	1/1	Must use

Description: Code which indicates an allowance or charge for the service specified

CodeList Summary (Total Codes: 7, Included: 1)

<u>Code</u>	<u>Name</u>
A	Allowance

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SAC02	1300	Service, Promotion, Allowance, or Charge Code	X	ID	4/4	Must use

Description: Code identifying the service, promotion, allowance, or charge

CodeList Summary (Total Codes: 1053, Included: 1)

<u>Code</u>	<u>Name</u>
ZZZZ	Mutually Defined if not one of the following:
G020	Bottle redemption/CRV charges(Alcohol ONLY)
H850	Taxes
H650	Tax for Hawaii DC only
D240	Freight

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SAC05	610	Amount	O	N2	1/15	Must use

Description: Monetary amount

SAC12	331	Allowance or Charge Method of Handling Code	O	ID	2/2	Must use
-------	-----	---	---	----	-----	----------

Description: Code indicating method of handling for an allowance or charge

CodeList Summary (Total Codes: 22, Included: 1)

<u>Code</u>	<u>Name</u>
02	Off Invoice

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SAC15	352	Description	X	AN	1/80	Must use

Description: A free-form description to clarify the related data elements and their content

Syntax Rules:

1. R0203 - At least one of SAC02 or SAC03 is required.
2. P0304 - If either SAC03 or SAC04 is present, then the other is required.
3. P0607 - If either SAC06 or SAC07 is present, then the other is required.
4. P0910 - If either SAC09 or SAC10 is present, then the other is required.
5. C1110 - If SAC11 is present, then SAC10 is required.

6. L130204 - If SAC13 is present, then at least one of SAC02 or SAC04 is required.
7. C1413 - If SAC14 is present, then SAC13 is required.
8. C1615 - If SAC16 is present, then SAC15 is required.

Semantics:

1. If SAC01 is "A" or "C", then at least one of SAC05, SAC07, or SAC08 is required.
2. SAC05 is the total amount for the service, promotion, allowance, or charge.
3. If SAC05 is present with SAC07 or SAC08, then SAC05 takes precedence.
4. SAC08 is the allowance or charge rate per unit.
5. SAC10 and SAC11 is the quantity basis when the allowance or charge quantity is different from the purchase order or invoice quantity.
6. SAC10 and SAC11 used together indicate a quantity range, which could be a dollar amount, that is applicable to service, promotion, allowance, or charge.
7. SAC13 is used in conjunction with SAC02 or SAC04 to provide a specific reference number as identified by the code used.
8. SAC14 is used in conjunction with SAC13 to identify an option when there is more than one option of the promotion.
9. SAC16 is used to identify the language being used in SAC15.

Comments:

1. SAC04 may be used to uniquely identify the service, promotion, allowance, or charge. In addition, it may be used in conjunction to further the code in SAC02.
2. In some business applications, it is necessary to advise the trading partner of the actual dollar amount that a particular allowance, charge, or promotion was based on to reduce ambiguity. This amount is commonly referred to as "Dollar Basis Amount". It is represented in the SAC segment in SAC10 using the qualifier "DO" - Dollars in SAC09.

Loop Invoice Shipment Summary

Pos: 060	Repeat: >1
	Optional
Loop: ISS	Elements: N/A

User Option (Usage): Must use

Purpose: To specify summary details of total items shipped in terms of quantity, weight, and volume

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
060	ISS	Invoice Shipment Summary	O	1		Must use

ISS Invoice Shipment Summary

Pos: 060	Max: 1
Summary - Optional	
Loop: ISS	Elements: 2

User Option (Usage): Must use

Purpose: To specify summary details of total items shipped in terms of quantity, weight, and volume

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISS01	382	Number of Units Shipped	X	R	1/10	Must use
Description: Numeric value of units shipped in manufacturer's shipping units for a line item or transaction set						
ISS02	355	Unit or Basis for Measurement Code	X	ID	2/2	Must use
Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken						
CodeList Summary (Total Codes: 794, Included: 1)						
		<u>Code</u>		<u>Name</u>		
		CA		Case		

Syntax Rules:

1. R010305 - At least one of ISS01, ISS03 or ISS05 is required.
2. P0102 - If either ISS01 or ISS02 is present, then the other is required.
3. P0304 - If either ISS03 or ISS04 is present, then the other is required.
4. P0506 - If either ISS05 or ISS06 is present, then the other is required.

Semantics:

1. ISS07 is the quantity of third party pallets.
2. ISS08 is the gross weight of third party pallets in pounds.

CTT Transaction Totals

Pos: 070	Max: 1
Summary - Optional	
Loop: N/A	Elements: 1

User Option (Usage): Must use

Purpose: To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	NO	1/6	Must use

Description: Total number of line items in the transaction set

Syntax Rules:

1. P0304 - If either CTT03 or CTT04 is present, then the other is required.
2. P0506 - If either CTT05 or CTT06 is present, then the other is required.

Comments:

1. This segment is intended to provide hash totals to validate transaction completeness and correctness.

SE Transaction Set Trailer

Pos: 080	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments	M	N0	1/10	Must use
		Description: Total number of segments included in a transaction set including ST and SE segments				
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
		Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set				

Comments:

1. SE is the last segment of each transaction set.

GE Functional Group Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GE01	97	Number of Transaction Sets Included	M	N0	1/6	Must use
		Description: Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element				
GE02	28	Group Control Number	M	N0	1/9	Must use
		Description: Assigned number originated and maintained by the sender				

Semantics:

1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Comments:

1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header.

IEA Interchange Control Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To define the end of an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	I16	Number of Included Functional Groups	M	N0	1/5	Must use
		Description: A count of the number of functional groups included in an interchange				
IEA02	I12	Interchange Control Number	M	N0	9/9	Must use
		Description: A control number assigned by the interchange sender				

810 – DC Invoice Example v4010:

ISA*00* *00* *01*Vendor ID*ZZ*CVSD*091201*0236*U*00401*000004688*0*P*^~
 GS*IN*Vendor ID*CVSD*20091201*0236*1843*X*004010~
 ST*810*000006638~
 BIG*20091130*02709444*20091021*2562120~
 REF*VR*9999~
 N1*ST*CVS DISTRIBUTION, INC*54*N101~
 N1*RE*Vendor Name*9*009999999~
 ITD*01*15*****60~
 DTM*011*20091128~
 FOB*PP*OR*FREDERICKPA 17026~
 IT1**83*CA*33.72*CP*UI*01000999999*PI*999999~
 PID*F****Item Description~
 PO4*12~
 TDS*277077*277077*277077~
 SAC*A*ZZZZ***2799*****02***SPOILS/DAMAGES~
 ISS*83*CA~
 CTT*1~
 SE*16*000006638~
 ST*810*000006639~
 BIG*20091130*02709655*20091120*4692402~
 REF*VR*9999~
 N1*ST*CVS DISTRIBUTION, INC*54*I101~
 N1*RE*Vendor Name*9*009999999~
 ITD*01*15*****60~
 DTM*011*20091130~
 FOB*PP*OR*FREDERICKPA 17026~
 IT1**200*CA*7.8*CP*UI*01000999999*PI*999999~
 PID*F**** Item Description~
 PO4*6~
 TDS*154440*154440*154440~
 SAC*A*ZZZZ***1560*****02***SPOILS/DAMAGES~
 ISS*200*CA~
 CTT*1~
 SE*16*000006639~
 GE*2*1843~
 IEA*1*000004688~