

**CVS/Caremark**

**Implementation Guide**

**824 – Application Advice**

**Version X12-4010**

# Table of Contents

<b>824</b>	<b>Application Advice</b> .....	<b>3</b>
<b>ISA</b>	<b>Interchange Control Header</b> .....	<b>5</b>
<b>GS</b>	<b>Functional Group Header</b> .....	<b>7</b>
<b>ST</b>	<b>Transaction Set Header</b> .....	<b>9</b>
<b>BGN</b>	<b>Beginning Segment</b> .....	<b>10</b>
<b>N1</b>	<b>Loop Name</b> .....	<b>11</b>
<b>N1</b>	<b>Name</b> .....	<b>12</b>
<b>PER</b>	<b>Administrative Communications Contact</b> .....	<b>13</b>
<b>OTI</b>	<b>Loop Original Transaction Identification</b> .....	<b>14</b>
<b>OTI</b>	<b>Original Transaction Identification</b> .....	<b>15</b>
<b>REF</b>	<b>Reference Identification</b> .....	<b>17</b>
<b>DTM</b>	<b>Date/Time Reference</b> .....	<b>18</b>
<b>AMT</b>	<b>Monetary Amount</b> .....	<b>19</b>
<b>TED</b>	<b>Loop Technical Error Description</b> .....	<b>20</b>
<b>TED</b>	<b>Technical Error Description</b> .....	<b>21</b>
<b>SE</b>	<b>Transaction Set Trailer</b> .....	<b>22</b>
<b>GE</b>	<b>Functional Group Trailer</b> .....	<b>23</b>
<b>IEA</b>	<b>Interchange Control Trailer</b> .....	<b>24</b>

Application Advice usage at CVS has been designed to relay any ‘Critical Error Messages’ to the Trading Partner that will affect the payment of Invoice(s) sent to CVS through the current EDI process. Please note that it is **MANDATORY** to trade the Application Advice (824) when conducting electronic invoicing.

**A Functional Acknowledgment (997) required back to CVS.**

Resend **ONLY** those invoices with corrected errors. **If the entire batch is resent, ALL invoices will be rejected and not paid.**

**Also Note - If you receive any error messages your invoice will not be paid.**

# 824 Application Advice

## Functional Group=AG

**Purpose:** This Draft Standard for Trial Use contains the format and establishes the data contents of the Application Advice Transaction Set (824) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide the ability to report the results of an application system's data content edits of transaction sets. The results of editing transaction sets can be reported at the functional group and transaction set level, in either coded or free-form format. It is designed to accommodate the business need of reporting the acceptance, rejection or acceptance with change of any transaction set. The Application Advice should not be used in place of a transaction set designed as a specific response to another transaction set (e.g., purchase order acknowledgment sent in response to a purchase order).

### Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	ISA	Interchange Control Header	M	1			Must use
	GS	Functional Group Header	M	1			Must use

### Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	ST	Transaction Set Header	M	1			Must use
020	BGN	Beginning Segment	M	1			Must use
<b>LOOP ID - N1</b>					<b>≥1</b>		
030	N1	Name	O	1			Must use
080	PER	Administrative Communications Contact	O	3			Used

### Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
<b>LOOP ID - OTI</b>					<b>≥1</b>	<b>N2/010L</b>	
010	OTI	Original Transaction Identification	M	1		N2/010	Must use
020	REF	Reference Identification	O	12		N2/020	Must use
030	DTM	Date/Time Reference	O	2		N2/030	Must use
050	AMT	Monetary Amount	O	>1		N2/050	Must use
<b>LOOP ID - TED</b>					<b>≥1</b>		
070	TED	Technical Error Description	O	1			Must use
090	SE	Transaction Set Trailer	M	1			Must use

### Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	GE	Functional Group Trailer	M	1			Must use

IEA Interchange Control Trailer M 1 Must use

**Notes:**

- 2/010L The OTI loop is intended to provide a unique identification of the transaction set that is the subject of this application acknowledgment.
- 2/010 The OTI loop is intended to provide a unique identification of the transaction set that is the subject of this application acknowledgment.
- 2/030 The DTM segment allows for the provision of date, time, or date and time information required to uniquely identify the original transaction set.
- 2/050 The AMT segment should be utilized if monetary amount information is important to the unique identification of the original transaction set.

# ISA Interchange Control Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 16

**User Option (Usage):** Must use

**Purpose:** To start and identify an interchange of zero or more functional groups and interchange-related control segments

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA01	I01	Authorization Information Qualifier	M	ID	2/2	Must use

**Description:** Code to identify the type of information in the Authorization Information

**CodeList Summary** (Total Codes: 7, Included: 1)

<u>Code</u>	<u>Name</u>
00	No Authorization Information Present (No Meaningful Information in I02)

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA02	I02	Authorization Information	M	AN	10/10	Must use

**Description:** Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)

ISA03	I03	Security Information Qualifier	M	ID	2/2	Must use
-------	-----	--------------------------------	---	----	-----	----------

**Description:** Code to identify the type of information in the Security Information

**CodeList Summary** (Total Codes: 2, Included: 1)

<u>Code</u>	<u>Name</u>
00	No Security Information Present (No Meaningful Information in I04)

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA04	I04	Security Information	M	AN	10/10	Must use

**Description:** This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)

ISA05	I05	Interchange ID Qualifier	M	ID	2/2	Must use
-------	-----	--------------------------	---	----	-----	----------

**Description:** Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified

**CodeList Summary** (Total Codes: 38, Included: 1)

<u>Code</u>	<u>Name</u>
01	Duns (Dun & Bradstreet)

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA06	I06	Interchange Sender ID	M	AN	15/15	Must use

**Description:** Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element

ISA07	I05	Interchange ID Qualifier	M	ID	2/2	Must use
-------	-----	--------------------------	---	----	-----	----------

**Description:** Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified

**CodeList Summary** (Total Codes: 38, Included: 1)

<u>Code</u>	<u>Name</u>
08	UCC EDI Communications ID (Comm ID)

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA08	I07	Interchange Receiver ID	M	AN	15/15	Must use

**Description:** Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID, thus other parties sending to them will use this as a receiving ID to route

data to them

ISA09	I08	<b>Interchange Date</b>	M	DT	6/6	Must use
		<b>Description:</b> Date of the interchange				
ISA10	I09	<b>Interchange Time</b>	M	TM	4/4	Must use
		<b>Description:</b> Time of the interchange				
ISA11	I10	<b>Interchange Control Standards Identifier</b>	M	ID	1/1	Must use
		<b>Description:</b> Code to identify the agency responsible for the control standard used by the message that is enclosed by the interchange header and trailer <b>All valid standard codes are used. (Total Codes: 1)</b>				
ISA12	I11	<b>Interchange Control Version Number</b>	M	ID	5/5	Must use
		<b>Description:</b> Code specifying the version number of the interchange control segments				
		<b>CodeList Summary</b> (Total Codes: 14, Included: 1)				
		<u>Code</u>		<u>Name</u>		
		00401		Draft Standards for Trial Use Approved for Publication by ASC X12 Procedures Review Board through October 1997		

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA13	I12	<b>Interchange Control Number</b>	M	N0	9/9	Must use

**Description:** A control number assigned by the interchange sender

ISA14	I13	<b>Acknowledgment Requested</b>	M	ID	1/1	Must use
		<b>Description:</b> Code sent by the sender to request an interchange acknowledgment (TA1)				
		<b>CodeList Summary</b> (Total Codes: 2, Included: 1)				
		<u>Code</u>		<u>Name</u>		
		0		No Acknowledgment Requested		

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA15	I14	<b>Usage Indicator</b>	M	ID	1/1	Must use

**Description:** Code to indicate whether data enclosed by this interchange envelope is test, production or information

**CodeList Summary** (Total Codes: 3, Included: 1)

<u>Code</u>	<u>Name</u>
P	Production Data

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA16	I15	<b>Component Element Separator</b>	M		1/1	Must use

**Description:** Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator

**GS****Functional Group Header**

<b>Pos:</b>	<b>Max: 1</b>
<b>Not Defined - Mandatory</b>	
<b>Loop: N/A</b>	<b>Elements: 8</b>

**User Option (Usage):** Must use**Purpose:** To indicate the beginning of a functional group and to provide control information**Element Summary:**

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS01	479	<b>Functional Identifier Code</b>	M	ID	2/2	Must use

**Description:** Code identifying a group of application related transaction sets**CodeList Summary** (Total Codes: 240, Included: 1)

<u>Code</u>	<u>Name</u>
AG	Application Advice (824)

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS02	142	<b>Application Sender's Code</b>	M	AN	2/15	Must use

**Description:** Code identifying party sending transmission; codes agreed to by trading partners

GS03	124	<b>Application Receiver's Code</b>	M	AN	2/15	Must use
------	-----	------------------------------------	---	----	------	----------

**Description:** Code identifying party receiving transmission; codes agreed to by trading partners

GS04	373	<b>Date</b>	M	DT	8/8	Must use
------	-----	-------------	---	----	-----	----------

**Description:** Date expressed as CCYYMMDD

GS05	337	<b>Time</b>	M	TM	4/8	Must use
------	-----	-------------	---	----	-----	----------

**Description:** Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)

GS06	28	<b>Group Control Number</b>	M	N0	1/9	Must use
------	----	-----------------------------	---	----	-----	----------

**Description:** Assigned number originated and maintained by the sender

GS07	455	<b>Responsible Agency Code</b>	M	ID	1/2	Must use
------	-----	--------------------------------	---	----	-----	----------

**Description:** Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480**CodeList Summary** (Total Codes: 2, Included: 1)

<u>Code</u>	<u>Name</u>
X	Accredited Standards Committee X12

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS08	480	<b>Version / Release / Industry Identifier Code</b>	M	AN	1/12	Must use

**Description:** Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed**CodeList Summary** (Total Codes: 39, Included: 1)

<u>Code</u>	<u>Name</u>
004010	Draft Standards Approved for Publication by ASC X12 Procedures Review Board through October 1997

**Semantics:**

1. GS04 is the group date.
2. GS05 is the group time.

3. The data interchange control number GS06 in this header must be identical to the same data element in the associated functional group trailer, GE02.

**Comments:**

1. A functional group of related transaction sets, within the scope of X12 standards, consists of a collection of similar transaction sets enclosed by a functional group header and a functional group trailer.



# ST Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

**User Option (Usage):** Must use

**Purpose:** To indicate the start of a transaction set and to assign a control number

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use

**Description:** Code uniquely identifying a Transaction Set

**CodeList Summary** (Total Codes: 298, Included: 1)

<u>Code</u>	<u>Name</u>
824	Application Advice

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST02	329	Transaction Set Control Number	M	AN	4/9	Must use

**Description:** Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set

## Semantics:

1. The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

# BGN Beginning Segment

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 3

**User Option (Usage):** Must use

**Purpose:** To indicate the beginning of a transaction set

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BGN01	353	Transaction Set Purpose Code	M	ID	2/2	Must use

**Description:** Code identifying purpose of transaction set

**CodeList Summary** (Total Codes: 65, Included: 1)

<u>Code</u>	<u>Name</u>
34	Payment Declined

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BGN02	127	Reference Identification	M	AN	1/30	Must use

**Description:** Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

TP and Date

BGN03	373	Date	M	DT	8/8	Must use
-------	-----	------	---	----	-----	----------

**Description:** Date expressed as CCYYMMDD

## Syntax Rules:

1. C0504 - If BGN05 is present, then BGN04 is required.

## Semantics:

1. BGN02 is the transaction set reference number.
2. BGN03 is the transaction set date.
3. BGN04 is the transaction set time.
4. BGN05 is the transaction set time qualifier.
5. BGN06 is the transaction set reference number of a previously sent transaction affected by the current transaction.

# Loop Name

<b>Pos: 030</b>	<b>Repeat: &gt;1</b>
<b>Optional</b>	
<b>Loop: N1</b>	<b>Elements: N/A</b>

**User Option (Usage):** Must use

**Purpose:** To identify a party by type of organization, name, and code

## Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
030	N1	Name	O	1		Must use
080	PER	Administrative Communications Contact	O	3		Used

<b>N1</b>	<b>Name</b>	<b>Pos: 030</b>	<b>Max: 1</b>
		<b>Heading - Optional</b>	
		<b>Loop: N1</b>	<b>Elements: 2</b>

**User Option (Usage):** Must use

**Purpose:** To identify a party by type of organization, name, and code

**Element Summary:**

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use

**Description:** Code identifying an organizational entity, a physical location, property or an individual

**CodeList Summary** (Total Codes: 1312, Included: 2)

<u>Code</u>	<u>Name</u>
FR	Message From
TO	Message To

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N102	93	Name	X	AN	1/60	Must use

**Description:** Free-form name

**Syntax Rules:**

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

**Comments:**

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

# PER Administrative Communications Contact

Pos: 080	Max: 3
Heading - Optional	
Loop: N1	Elements: 4

**User Option (Usage):** Used

**Purpose:** To identify a person or office to whom administrative communications should be directed

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PER01	366	Contact Function Code	M	ID	2/2	Must use

**Description:** Code identifying the major duty or responsibility of the person or group named

**CodeList Summary** (Total Codes: 230, Included: 1)

<u>Code</u>	<u>Name</u>
AA	Authorized Representative

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PER02	93	Name	O	AN	1/60	Must use

**Description:** Free-form name

'EDI HOT LINE'

PER03	365	Communication Number Qualifier	X	ID	2/2	Must use
-------	-----	--------------------------------	---	----	-----	----------

**Description:** Code identifying the type of communication number

**CodeList Summary** (Total Codes: 40, Included: 1)

<u>Code</u>	<u>Name</u>
TE	Telephone

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PER04	364	Communication Number	X	AN	1/80	Must use

**Description:** Complete communications number including country or area code when applicable

'401-770-4475'

## Syntax Rules:

1. P0304 - If either PER03 or PER04 is present, then the other is required.
2. P0506 - If either PER05 or PER06 is present, then the other is required.
3. P0708 - If either PER07 or PER08 is present, then the other is required.

# Loop Original Transaction Identification

<b>Pos: 010</b>	<b>Repeat: &gt;1</b>
<b>Mandatory</b>	
<b>Loop: OTI</b>	<b>Elements: N/A</b>

**User Option (Usage):** Must use

**Purpose:** To identify the edited transaction set and the level at which the results of the edit are reported, and to indicate the accepted, rejected, or accepted-with-change edit result

## Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	OTI	Original Transaction Identification	M	1		Must use
030	DTM	Date/Time Reference	O	2		Must use
050	AMT	Monetary Amount	O	>1		Must use
070		Loop TED	O		>1	Must use

# OTI Original Transaction Identification

Pos: 010	Max: 1
Detail - Mandatory	
Loop: OTI	Elements: 4

**User Option (Usage):** Must use

**Purpose:** To identify the edited transaction set and the level at which the results of the edit are reported, and to indicate the accepted, rejected, or accepted-with-change edit result

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
OTI01	110	Application Acknowledgment Code	M	ID	1/2	Must use

**Description:** Code indicating the application system edit results of the business data

**CodeList Summary** (Total Codes: 20, Included: 1)

<u>Code</u>	<u>Name</u>
TR	Transaction Set Reject

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
OTI02	128	Reference Identification Qualifier	M	ID	2/3	Must use

**Description:** Code qualifying the Reference Identification

**CodeList Summary** (Total Codes: 1503, Included: 1)

<u>Code</u>	<u>Name</u>
TN	Transaction Reference Number

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
OTI03	127	Reference Identification	M	AN	1/30	Must use

**Description:** Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Invoice Number

OTI10	143	Transaction Set Identifier Code	O	ID	3/3	Must use
-------	-----	---------------------------------	---	----	-----	----------

**Description:** Code uniquely identifying a Transaction Set

**CodeList Summary** (Total Codes: 298, Included: 1)

<u>Code</u>	<u>Name</u>
810	Invoice

## Syntax Rules:

1. C0908 - If OTI09 is present, then OTI08 is required.

## Semantics:

1. OTI03 is the primary reference identification or number used to uniquely identify the original transaction set.
2. OTI06 is the group date.
3. OTI07 is the group time.
4. If OTI11 is present, it will contain the version/release under which the original electronic transaction was translated by the receiver.
5. OTI12 is the purpose of the original transaction set, and is used to assist in its unique identification.
6. OTI13 is the type of the original transaction set, and is used to assist in its unique identification.
7. OTI14 is the application type of the original transaction set, and is used to assist in its unique identification.
8. OTI15 is the type of action indicated or requested by the original transaction set, and is used to assist in its unique identification.
9. OTI16 is the action requested by the original transaction set, and is used to assist in its unique identification.
10. OTI17 is the status reason of the original transaction set, and is used to assist in its unique identification.

## Comments:

1. OTI02 contains the qualifier identifying the business transaction from the original business application, and OTI03 will

- contain the original business application identification.
- 2. If used, OTI04 through OTI08 will contain values from the original electronic functional group generated by the sender.
- 3. If used, OTI09 through OTI10 will contain values from the original electronic transaction set generated by the sender.



# REF Reference Identification

Pos: 020	Max: 12
Detail - Optional	
Loop: OTI	Elements: 2

**User Option (Usage):** Must use  
**Purpose:** To specify identifying information

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

**Description:** Code qualifying the Reference Identification

**CodeList Summary** (Total Codes: 1503, Included: 1)

<u>Code</u>	<u>Name</u>
VR	Vendor ID Number

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF02	127	Reference Identification	X	AN	1/30	Must use

**Description:** Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier  
CVS Vendor Number

## Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

## Semantics:

1. REF04 contains data relating to the value cited in REF02.

# DTM Date/Time Reference

Pos: 030	Max: 2
Detail - Optional	
Loop: OTI	Elements: 2

**User Option (Usage):** Must use  
**Purpose:** To specify pertinent dates and times

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use

**Description:** Code specifying type of date or time, or both date and time

**CodeList Summary** (Total Codes: 1112, Included: 1)

<u>Code</u>	<u>Name</u>
003	Invoice

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM02	373	Date	X	DT	8/8	Must use

**Description:** Date expressed as CCYYMMDD  
 Invoice Date

## Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.
3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

# AMT Monetary Amount

Pos: 050	Max: >1
Detail - Optional	
Loop: OTI	Elements: 2

**User Option (Usage):** Must use

**Purpose:** To indicate the total monetary amount

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
AMT01	522	Amount Qualifier Code	M	ID	1/3	Must use

**Description:** Code to qualify amount

**CodeList Summary** (Total Codes: 1473, Included: 1)

<u>Code</u>	<u>Name</u>
OP	Original Payment Total

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
AMT02	782	Monetary Amount	M	R	1/18	Must use

**Description:** Monetary amount

Invoice Amount

# Loop Technical Error Description

Pos: 070	Repeat: >1
Optional	
Loop: TED	Elements: N/A

**User Option (Usage):** Must use

**Purpose:** To identify the error and, if feasible, the erroneous segment, or data element, or both

## Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
070	TED	Technical Error Description	O	1		Must use

# TED Technical Error Description

Pos: 070	Max: 1
Detail - Optional	
Loop: TED	Elements: 2

**User Option (Usage):** Must use

**Purpose:** To identify the error and, if feasible, the erroneous segment, or data element, or both

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TED01	647	Application Error Condition Code	M	ID	1/3	Must use

**Description:** Code indicating application error condition

**CodeList Summary** (Total Codes: 162, Included: 1)

<u>Code</u>	<u>Name</u>
024	Other Unlisted Reason

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TED02	3	Free Form Message	O	AN	1/60	Must use

**Description:** Free-form text  
Error Message/Condition

## Comments:

1. If used, TED02 will contain a generic description of the data in error (e.g., part number, date, reference number, etc.).

# SE Transaction Set Trailer

Pos: 090	Max: 1
Detail - Mandatory	
Loop: N/A	Elements: 2

**User Option (Usage):** Must use

**Purpose:** To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	<b>Number of Included Segments</b>	M	N0	1/10	Must use
<b>Description:</b> Total number of segments included in a transaction set including ST and SE segments						
SE02	329	<b>Transaction Set Control Number</b>	M	AN	4/9	Must use
<b>Description:</b> Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set						

## Comments:

1. SE is the last segment of each transaction set.

# GE Functional Group Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

**User Option (Usage):** Must use

**Purpose:** To indicate the end of a functional group and to provide control information

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GE01	97	<b>Number of Transaction Sets Included</b>	M	N0	1/6	Must use
<b>Description:</b> Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element						
GE02	28	<b>Group Control Number</b>	M	N0	1/9	Must use
<b>Description:</b> Assigned number originated and maintained by the sender						

## Semantics:

1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

## Comments:

1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header.

# IEA Interchange Control Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

**User Option (Usage):** Must use

**Purpose:** To define the end of an interchange of zero or more functional groups and interchange-related control segments

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	I16	<b>Number of Included Functional Groups</b>	M	N0	1/5	Must use
		<b>Description:</b> A count of the number of functional groups included in an interchange				
IEA02	I12	<b>Interchange Control Number</b>	M	N0	9/9	Must use
		<b>Description:</b> A control number assigned by the interchange sender				



**824 – Application Advice Example v4010:**

ISA\*00\*           \*00\*           \*ZZ\*CVS   \*08\*"Vendor ID\*091018\*0411\*U\*00401\*000007847\*0\*P\*^~  
 GS\*AG\*CVS\*Vendor ID\*20091018\*0411\*530\*X\*004010~  
 ST\*824\*0532~  
 BGN\*34\*0099   20091017\*20091017~  
 N1\*TO\*Company Name~  
 N1\*FR\*CVS/PHARMACY~  
 PER\*AA\*EDI HOTLINE\*TE\*401-770-4475~  
 OTI\*TR\*TN\*6371647\*\*\*\*\*810~  
 REF\*VR\*19999~  
 DTM\*003\*20090824~  
 AMT\*OP\*3360~  
 TED\*024\*99999990099PO401000001           CASE PACK ERROR\*\*1~  
 TED\*024\*99902199999IT1 00003700009090 PRODUCT ID NOT ON FILE\*\*2~  
 SE\*10\*0532~  
 GE\*1\*530~  
 IEA\*1\*000007847~